

**SPECTRAL FILTER**

**Patent number:** JP1310302  
**Publication date:** 1989-12-14  
**Inventor:** KAWAZOE SHOZO; others: 01  
**Applicant:** NITTO DENKO CORP  
**Classification:**  
**- international:** G02B5/08  
**- european:**  
**Application number:** JP19880142263 19880609  
**Priority number(s):**

**Report a data error here**

**Abstract of JP1310302**

**PURPOSE:** To obviate the generation of a large difference in hue between incident light as well as transmitted light and reflected light by successively laminating a metallic film and dielectric film having prescribed film thicknesses on one face of a transparent base body and confining the fluctuation in the visible ray transmittance to a prescribed value or below.

**CONSTITUTION:** The thin dielectric film 2, the thin metallic film 3 having 50-250Å film thickness and the tin dielectric film 4 having 300-1,500Å film thickness are successively laminated on one face of the transparent base body 1. The fluctuation in the entire region of 400-800nm visible region of visible ray transmittance is confined to  $\leq +$  or  $-15\%$  of the central value, i.e.  $(\text{max. transmittance} + \text{min. transmittance}) \times 1/2$  and the fluctuation of visible ray reflectivity is confined to  $\leq +$  or  $-15\%$  of the central value, i.e.  $(\text{max. reflectivity} + \text{min. reflectivity}) \times 1/2$ . The incident light is separated to the transmitted light and the reflected light in such a manner. The spectral filter which decreases the absorption loss of light and can bisect the incident light nearly to the transmitted light and the reflected light is obtained.



---

Data supplied from the **esp@cenet** database - Patent Abstracts of Japan